


Espero BV

Sluisweg 26-28
5145 PE Waalwijk
The Netherlands
T +31 (0)416 338955
F +31 (0)416 332635
E info@espero.nl
I www.espero.net

general description
folding partitions
UNO & DUPLO



Espero mobile partitions efficiently divide space with the utmost ease and flexibility. Whether the requirement is acoustics, aesthetics, ease of use or cost effectiveness Espero has the answer.

The Uno and Duplo range of folding partitions are the most cost effective means of dividing space. These partitions are timber based, consisting of narrow panels of high quality chipboard joined by continuous PVC profiled strip hinges. The individual panels can be finished in virtually any material used in interior design. Lacquered in any colour; high quality wood veneers, hard plastics, melamine, etc.

The Uno is a single skinned partition while the Duplo is double walled to provide enhanced acoustics and greater stability. The Uno, as standard, has limited sound insulating value but can be produced in the 'A' execution which includes a sound insulating PVC sweep seal (and also draught insulating) which increases the Rw value to 28dB (estimated laboratory value). The Duplo is internally reinforced by steel hinges and sound insulating materials are sandwiched between each facing board. The standard Duplo has a Rw value of 41dB (estimated laboratory value) but can be produced in the 'S' execution which increases the Rw value to 43dB (est. Lab value).

The Uno and Duplo are suspended from a top track by means of double wheeled trolleys moving the walls along without the need of a floor track. The track of this wall is also available in a curved angle where the radius is not smaller than 920mm. The panels run mono directionally but this does not reduce the flexibility of the partitions. Each wall is built up by a series of wings which inter-connect to form the wall (see schematic drawings).

This means that the wall can be:


- one single wing which opens on one side only as is fixed at the other side to the wall (max. 6000 mm).
- one single wing which opens at both sides - a floating wing (max. 6000 mm)
- two wings fixed at the ends and meeting in the middle (max. 2 x 6000 mm)
- one wing fixed at one side and one wing floating (max. 2 x 6000 mm)
- two wings fixed and one wing floating (max. 3 x 6000 mm)
- etcetera, the number of combinations are endless.

The end of each wing is finished with an end post which inter-connect with either a wall jamb or another end post depending on the layout of the wall (see above). Each wall post is supplied with a door handle and latch system which can if needed be lockable.

Where appropriate the wall can be also be specially designed to fit in a custom made niche. To reduce the number of panels needed a sliding niche panel is attached to the end post – therefore sealing the pocket when the wall is in the closed position.

Due to the hinged system the wall can be open and closed in one easy and quick movement. This makes the Uno and Duplo ideally suitable for areas of high usage and equally because there is very little maintenance required.

The content of this Technical Data Sheet have been completely brought up to date.
Espero BV has the right to make amendments without giving notice in advance.
Data sheet number: 00.ESP09.2009

Espero BV Sluisweg 26-28 5145 PE Waalwijk The Netherlands T +31 (0)416 338955 F +31 (0)416 332635 E info@espero.nl I www.espero.net	folding partition UNO		
Type	Uno 6	Uno 8	Uno 12
Characteristics/Application	For use in small areas: living areas/above counters and bars.	For use in medium to large areas i.e. church halls.	For use in large areas.
Panel sizes: Panel Width Package/Stacking Width Height Wing Length*	150 mm 175 mm Maximum 3100 mm Max.Wing Length 6000 mm	196 mm 225 mm Maximum 3300 mm Max.Wing Length 6000 mm	296 mm 325 mm Maximum 3300 mm Max.Wing Length 6000 mm
Deviating specifications by request.			
Package Thickness when stacked:	100 mm/ml + 120 mm for each closing post/end post.	80 mm/ml + 120 mm for each closing post/end post.	60 mm/ml + 120 mm for each closing post/end post.
Above calculations are approx. Exact sizes available upon request.			
*Wall/Opening Width	Wall opening width is unlimited but must be built up in a series of wings. Please see schematic to see possible combinations.		
Width of Recess-when used	300 mm	350 mm	450 mm
Hinges	profiled extruded PVC		
Boards	High quality E1 chipboards 12mm (680 - 720 kg/m ³)		
Sound Insulation Rw-value (estimated laboratory values)	Limited	'A' execution = 28 dB	
Finishes to Board Surface	All normal finishes that are used in interiors		
Weight m ²	15 kg/m ²	18 kg/m ²	20 kg/m ²
Top and bottom sealing of the panels	Standard execution has no top or bottom seals		'A' execution: Sweep seals top and bottom.
Closure of panel	The end panel is always a closure post. The closure post fits onto a aluminium extruded wall jamb. This panel is supplied with a door handle and latch which closes onto the wall jamb. If needed the closure post can be supplied with a Euro Cylinder lock.		
Track	Heavy-duty aluminium profile, 42x32mm (width x height)		
Multiple-wheel Trolleys	Steel ball bearings with plastic (PA/Nylon) surface for smooth and silent movement of the walls.		
Pelmet Boards	As standard 50mm wide x 32mm depth (total width = 142 mm, track + pelmets)		
Static behaviour	The panels may not be subjected to external forces or weights as the trolleys and tracks are designed for a specific load.		
Environmental constraints	1. Only suitable for inside use 2. Dry surroundings with maximum relative air-humidity of 60%		
Remarks	All aluminium profiles: EN AW-6060 T6 / YB6 - AA05 - VOM1		

The content of this Technical Data Sheet have been completely brought up to date.
Espero BV has the right to make amendments without giving notice in advance.
 Data sheet number: 01.ESP09.2005